

Features and Benefits

The Molex MOD-Clip 4 Pair UTP Termination Tool is a robust, reliable product that offers fast, fault-less gas-tight termination of all four pairs of the solid cable simultaneously. The Termination Tool Frame is manufactured of high grade steel and is used with die-cast Termination Heads.

Designed exclusively for use with Molex MOD-Clip UTP jacks, the Tool Frame is supplied unloaded on to which the UTP Termination Head is fitted. Only the MOD-Clip Tool Frame can be used to terminate UTP MOD-Clip Jacks. The MOD-Clip Tool Frame is distinguishable by the yellow Jack Pusher assembled into the Frame. To Terminate DataGate™ Jacks use the DataGate 4 Pair Termination Tool Frame which features a red Jack Pusher.

Operation is simple and efficient. Fit the Termination Head to the Tool Frame, lace the wires into the Termination Head, place the MOD-Clip Jack on to the Termination Head. Swivel the Head into the cutting position and squeeze the handles of the Frame. The result is a fully terminated Jack with all 8 wires firmly and accurately seated and neatly trimmed in a few quick and simple steps.

Fitting or changing the Termination Head on to the Tool Frame is easy. Simply screw the Head into place with the Allen key provided. The ergonomic design of the Termination Tool Frame Handles provides comfortable repeat operation.

- Designed exclusively for the termination of UTP MOD-Clip Jacks.
- Yellow Jack Pusher distinguishes the MOD-Clip Tool Frame from DataGate Tool Frame.
- Fast and simple termination procedure.
- Cables are terminated neatly and accurately in a few simple steps.
- Tool Frame and Termination Head are supplied separately.
- Robust Tool Frame and Termination Head construction.
- Ergonomic Tool Handles for comfortable repeat operation

Technical Information

Mechanical Characteristics

Material
 Tool Frame: High Carbon Steel
 Termination Heads: Zinc Alloy
 Blades: High Carbon Steel
 Handle: Thermoplastic Rubber

Termination Head Wire Accommodation: 23-24 AWG solid conductors
 Cable Accommodation Types: Molex branded U/UTP cables

Shipping Weight
 Part No 31.0010: 480g
 Part No 31.0012: 35g each



Dimensions
 Termination Frame: 270mm (L) x 95mm (W) x 47mm (H)
 Termination Head: 80mm (L) x 40mm (W) x 20mm (H)

Reference Information

The UTP Termination Head is compatible with the following MOD-Clip Jack part numbers

Part Number	Description
MMC-00010-**	PowerCat 6 UTP MOD-Clip Jack
MMC-00013-0**	PowerCat 5E UTP MOD-Clip Jack

Note: For Termination of the C6A Shielded MOD-Clip Jacks, use the DataGate Termination Frame part no 31.0011 with the C6A Shielded Termination Head part no 31.0013 and remove the MOD-Clip nose piece before termination.



MOLEX PREMISE NETWORKS

Americas
 Tel: 630 969 4550
 www.molexpn.com

EMEA
 Tel: 44 (0)2392 205800
 www.molexpn.co.uk

APAC
 Tel: 61 3 9971 7111
 www.molexpn.com.au

ORDERING INFORMATION**molex** **MOD-Clip™ 4 Pair
UTP Termination
Tool**

Order No.	SAP No.	Description
31.0010	Consult Molex	MOD-Clip 4 Pair Termination Tool Frame
31.0012	Consult Molex	Termination Head UTP

MOLEX PREMISE NETWORKS

Americas
Tel: 630 969 4550
www.molexpn.com

EMEA
Tel: 44 (0)2392 205800
www.molexpn.co.uk

APAC
Tel: 61 3 9971 7111
www.molexpn.com.au