

# SLT3 Tester

The SLT3 Tester is a rugged, lightweight product designed to verify the integrity of 1-, 2-, 3-, and 4-pair UTP or STP channels. Incorporating a unique 3-in-1 design, this tester features built-in modular jacks for USOC, 568A and 568B wiring sequences, eliminating the need to attach separate converters or adapters. Powered by a 9 volt battery, this compact hand-held tester is ideal for anyone who wants to test the integrity of the wire mapping in their cabling system. The tester is available as a UTP only tester or an STP tester capable of testing UTP or Shielded Systems.

The Master and Remote units separate for end-to-end testing of installed cabling. Shorts, opens, reversals, or mis-wires are easily detected within seconds – the continuously-sequencing LED display immediately highlights any problems in the cabling system. Both pieces simply snap and lock together and a proximity switch disconnects the battery when not in use. Designed to fit neatly into a tool box or pocket, the SLT3 tester has a convenient “eye” feature for attaching to a belt or frame.

The SLT3 checks each channel from the Station Device to the System. In addition the SLT3 can test all line cords. The SLT3 tester verifies or indicates wiring errors on 2-, 3- and 4-pair UTP and STP channels.



## FEATURES AND ADVANTAGES

Innovative 3-in-1 design features modular jacks for testing USOC, 568A and 568B cabling systems

Accurately verifies the continuity and sequence of 1-, 2-, 3-, and 4 pair UTP and STP channels

Continuously-sequencing LED display provides a diagnostic readout that immediately detects shorts, opens, reversals and mis-wires at a glance

Simply snap and lock master and remote units together when not in use

Ergonomically designed hand-held unit is lightweight, rugged, and impact-resistant

9 Volt alkaline battery included

SLT3 performs shield continuity on STP systems

[www.molex.com/](http://www.molex.com/)

# SLT3 Tester

## SPECIFICATIONS

### Mechanical

**Material:** Thermoplastic UL94V-0  
Black Case, red latch

**Power Requirements:** 9V Alkaline Battery  
(included)

**Jack Contact Material:** 50 μinches gold over  
100μ inches nickel

### SLT3 Single Line Tester

**Set Dimensions:**  
146mm x 58mm x 38mm  
(5.75"H x 2.3"W x 1.5"D)

**Shipping Weight:**  
224g (8 oz.)

**Master Dimensions:**  
109mm x 58mm x 38mm  
(4.3"H x 2.3"W x 1.5"D)

**Shipping Weight:**  
140g (5 oz.)

**Remote Dimensions:**  
109mm x 58mm x 38mm  
(4.3"H x 2.3"W x 1.5"D)

**Shipping Weight:** 84g (3 oz.)

## ORDERING INFORMATION

Order No.	SAP No.	Description
33A-100-10	180390011	SLT3 Shielded Tester
33-100	180390001	SLT3 Tester UTP
33.D0020P	180390044	SLT3 Shielded Tester (Polish operating instructions)
33.B0020	180390005	SLT3 Tester UTP with carry case (available APAC only)