

DIN Rail Mountable DataGate Jack Adapter >

The DIN rail mountable jack adapter provides copper protection for terminated network cable with the DataGate jack. It can be mounted to a standard 35mm DIN rail and locked in place with a multi function clip, allowing it to mount on different types of DIN rail.

It accepts Molex C5e, C6 unshielded and C6A shielded DataGate jacks which snap in and out for easy moves, adds, and changes. Adapter is available in black.



FEATURES & ADVANTAGES

Supports Molex C5e, C6 unshielded and C6A shielded DataGate jacks

Compatible with 1 DataGate Jack

35mm standard DIN rail mountable to support standard 35mm DIN rail application

Ground screw provided

DIN Rail Clip Support EN60715 Standard profile (Hat shape) and G profile

SPECIFICATIONS

Mechanical

Material:

Shell: 1.2mm CRS with black powder coating

Jack Fascia: PC UL94V-0 in black

Dimensions:

22.6mm W x 78.2mm D x 56.3mm H

0.89" W x 3.08" D x 2.22"H

Environmental

Work Temperature:

-25°C to +65°C (32 to 104°F)

Relative Humidity:

≤85% (+30°C)

Shipping Weight: 112.5g

ORDERING INFORMATION

Order No.	SAP No.	Description
WFR-00118	182870011	DIN Rail-Unloaded DataGate Adapter STP/UTP

www.molex.com/products/fiber/enclosures/